

Practical

Quickcream is the latest innovation from Elmeco, leading Italian manufacturer of premium frozen and cold-drink beverages dispensers. It has been created for preparation and serving of premium soft ice-cream product. Thank to the user-friendly electronic touchpad and patented dispensing system Quickcream provides servings of approximately 70 grams (2.5 oz) each.

- Patented Total Cold refrigeration system keeps product at a constant temperature to the very last portion left in the machine
- The drive shaft of each Quickcream unit which is manufactured with a Seal-Less patent, makes it uniquely the most hygienic & safest product of its kind on the market today
- User friendly digital touchpad incorporates: portion control mechanism temperature and density control system programmable auto-defrost timer
- Innovative removable external condenser air-filter makes the periodical maintenance a snap



If you're looking for something better, you can go whistle for it.

Innovative design

With its compact dimensions, smooth design and bright colours, Quickcream's panels give an operator plenty of space for PoS (Point of Sales) materials. Quick and easy to disassemble, the machine guarantees maximum hygiene for milk-based products.

A blend of design and technology will increase not only your profits but also enhance look of your premises.

Respect for the environment

Thank to the brushless drive system, dual-speed production process and stand-by temperature settings, Quickcream reduces energy consumption and minimizes noise generated by internal components. In 90% Quickcream is made with recyclable and reusable materials, which perfectly reflects Elmeco's dedication to protect natural environment.

Technical specifications

MODELLO/MODEL	Quickcream 1
CAPACITA (LITRI)/LITRES	3-4 lt/0.79 gallon
PESO/WEIGHT	30 kg/65 lbs
DIMENSIONI/DIMENSION	depth: 471 mm/19" width: 276 mm/11" height: 712 mm/28"
POTENZA MACCHINA/ MACHINE POWER	420 watt
POTENZA COMPRESSORE/ COMPRESSOR POWER	300 watt 1/3 HP/2.6 A mps
VOLTAGGIO FREQUENZA/ VOLTAGE FREQUENCY	230 volts/50 hz 115 volts/60 hz

- Temperature control
Range between -6°C/21°F and -8°C/17.5°F in increments of 0.5°C/0.875°F
- Shaker system
Brushless low energy consumption
- Stand-by mixing velocity
50 Rpm
- Mixing velocity
70 Rpm



Available in



GREY
Pantone 441



PURPLE
Pantone 279



LILAC
Pantone 271



GREEN
Pantone 366